

# CCTV SYSTEMS & VEHICLE SAFETY



REVERSING	2-4
RECORDING SYSTEMS	4-6
DIRECT VISION (PSS)	8-11
FRONT   SIDE DETECTION SYSTEMS	11-12, 24
TELEMATICS	5, 13-14
MIRROR MONITOR KITS   BRAKE LIGHT CAMERAS	15-16
MONITORS	17-19
CAMERAS	19-22
RECORDERS	23
BRIGADE	24
LEADS   ACCESSORIES	25-27
WARNING   REVERSE ALARMS   BUZZERS	28-30

# **CCTV SYSTEMS & VEHICLE SAFETY REVERSING KITS**

## 4.3" MIRROR MOUNT REVERSING KIT

#### CCTV22

- 12 24 volt
- · Simple Installation over Existing Mirror
- Lens Angle 120° with Night Vision
- Camera Rated IP67
- Monitor: H.98 mm W.277 mm D.24 mm Camera: D.40 mm Dia.30 mm













INCORPORATES: Monitor | Camera | Full Fitting Kit

## 5" REVERSING KIT

#### CCTV23A

- 10 32 volt
- 3 Camera Inputs with Mirror or Normal Switching
- Lens Angle 120° with Night Vision
- Audio Function | Remote Control
- Monitor: H.117 mm W.157 mm D.30 mm (Excl. Visor) Camera: H.80 mm W.74 mm D.77 mm













INCORPORATES: Monitor MON23A | Camera CAM13A | Full Fitting Kit

# 5.6" REVERSING KIT

## CCTV13B

- 10 32 volt
- · 3 Camera Inputs with Mirror or Normal Switching
- Lens Angle 120° with Night Vision
- HD Compatible
- Audio Function | Remote Control
- Monitor: H.136 mm W.145 mm D.31 mm (Excl. Visor) Camera: H.65 mm W.90 mm D.55 mm













INCORPORATES: Monitor MON13B | Camera | Full Fitting Kit

# 5.6" REVERSING KIT

# CCTV14A

- 10 32 volt
- · 3 Camera Inputs with Mirror or Normal Switching
- Lens Angle 120° with Night Vision
- Audio Function | Remote Control
- Monitor: H.118 mm W.160 mm D.22 mm (Excl. Visor) Camera: H.80 mm W.74 mm D.77 mm













INCORPORATES: Monitor MON14A | Camera CAM13A | Full Fitting Kit

# CCTV SYSTEMS & VEHICLE SAFETY **REVERSING KITS**

# 5.6" REVERSING KIT WITH ROOF MOUNTED CAMERA

# CCTV18A

- 10 32 volt
- 3 Camera Inputs with Mirror or Normal Switching
- Lens Angle 150° with Night Vision
- · Audio Function | Remote Control
- Monitor: H.118 mm W.160 mm D.22 mm (Excl. Visor) Camera: H.100 mm W.130 mm D.210 mm











INCORPORATES: Monitor MON14A | Camera CAM18A | Full Fitting Kit

# 7" FULL 1080P HD REVERSING KIT WITH WEATHERPROOF MONITOR

#### CCTV19HD

- 10 32 volt
- 3 Camera Inputs with Mirror or Normal Switching
- Lens Angle 130° with Night Vision
- · Automatic self-adjusting resolution
- · Remote Control
- Camera Rated IP69K | Monitor Rated IP66k
- Monitor: H.132 mm W.197 mm D.35 mm (Excl. Visor)















## 7" REVERSING KIT

# CCTV24A

- 12 24 volt
- 2 Camera Inputs with Mirror or Normal Switching
- Lens Angle 120° with Night Vision
- · Audio Function | Remote Control
- Monitor: H.115 mm W.172 mm D.44 mm (Incl. Visor) Camera: H.80 mm W.74 mm D.77 mm

INCORPORATES: Monitor MON24A | Camera CAM13A | Full Fitting Kit













AUDIO FUNCTION

# 7" FULL 1080P HD CCTV REVERSING KITS

- 12 24 volt
- D1/720/1080P Auto Sensing
- Lens Angle 120° with Night Vision
- Camera Rated IP69K | ECE R10, EMC, CE Approved
- Audio Function | Remote Control
- Monitor: H.113 mm W.195 mm D.27 mm (Excl. Visor) Camera: H.77 mm W.90 mm D.70 mm

#### CCTV27HD

- · Single screen viewing
- · 3 Camera inputs with mirror or normal switching

INCORPORATES: Monitor MON27HD | Camera CAM30 | Full Fitting Kit





- · Single, split, triple or quad viewing options
- · 4 Camera inputs with mirror or normal switching

INCORPORATES:
Monitor MON27QHD | Camera CAM30 | Full Fitting Kit







# **CCTV SYSTEMS & VEHICLE SAFETY** RECORDING SYSTEMS

# 7" FULL 1080P HD DIGITAL WIRELESS REVERSING SYSTEM WITH DVR

#### CCTV15HD

- 10 32 volt
- 4 Programmable Camera Inputs
- 1 SD Card Slot up to 128GB (32GB Supplied)
- Lens Angle 120° with Night Vision | Audio Function | Remote Control
- Monitor: H.122 mm W.182 mm D.42 mm (Excl. Visor) Camera: H.72 mm W.98 mm D.70 mm

Recording Time (up to) 240 hrs 1 camera | 60 hrs 4 cameras Transmission (up to) 150mtrs no Barrier | 32mtrs with Barrier

INCORPORATES:
Monitor MON15HD | Camera CAM15HD | Full Fitting Kit



Before Installation check other before installation check other electronic equipment for Interference i.e. Bluetooth etc or check with our technical department.





7"

**(((1))**)







## 7" DIGITAL WIRELESS REVERSING SYSTEM WITH DVR

#### CCTV26D

- 10 32 volt
- · 4 Programmable Camera Inputs
- 1 SD Card Slot up to 128GB (32GB Supplied)
- Lens Angle 120° with Night Vision | Audio Function | Remote Control
- Monitor: H.140 mm W.190 mm D.76 mm (Incl. Visor) Camera: H.100 mm W.95 mm D.60 mm

Recording Time (up to) 240 hrs 1 camera, 60 hrs 4 cameras Transmission (up to) 150mtrs no Barrier, 32mtrs with Barrier

INCORPORATES: Monitor MON26D | Camera CAM26D | Full Fitting Kit













# 500GB FULL 1080P HD DIGITAL VIDEO RECORDER SYSTEM

# CCTVHDR4

- 10 32 volt
- 4 x 1080p HD Cameras | 4 Channel Digital Recorder
- Key Lockable Data Storage up to 1 x 2.5" 1TB SSD and 1 x 128GB SD Card
  - 500GB SSD Hard Drive Included
- · GPS Data | Remote Control
- Monitor: H.114 mm W.193 mm D.30 mm (Excl. Visor) DVR4HD: H.38 mm W.146 mm D.185 mm







LCD TOUCH SCREEN







INCORPORATES:
Recorder DVR4HD | Monitor MON30 | Camera CAM30, CAM31, CAM33 x2 | Full Fitting Kit

# 500GB FULL 1080P HD DIGITAL VIDEO RECORDER SYSTEM

# **CCTVHDR5**

- 10 32 volt
- 5 x 1080p HD Cameras
- 8 Channel Digital Recorder
- · Key Lockable Data Storage up to 1 x 2.5" 1TB SSD and 1 x 128GB SD Card
- 500GB SSD Hard Drive Included
- · GPS Data | Remote Control
- Monitor: H.114 mm W.193 mm D.30 mm (Excl. Visor) DVR6: H.100 mm W.226 mm D.225 mm

INCORPORATES: Recorder DVR6 | Monitor MON30 Camera CAM30, CAM32, CAM33 x2 | Full Fitting Kit















# **CCTV SYSTEMS & VEHICLE SAFETY BESPOKE SYSTEMS** | TELEMATICS

#### 1TB SSD 4 CAMERA HD BESPOKE DVR SYSTEM

#### **CCTVHDR7**

- 10 32 volt
- 4 x HD Cameras
- $\cdot$  Key Lockable Data Storage up to 1TB SSD and 1 x 128GB SD Card
- 1TB SSD (solid-state drive) Hard Drive Included
- GPS Data | External Cameras Rated IP67
- Panic/incident button manually mark and safeguard an incident
- Monitor: H.115 mm W.175 mm D.25 mm (Excl. Stand) DVR7HD: H.50 mm W.165 mm D.152 mm

#### INCORPORATES:

Recorder DVR7HD

Monitor MON70A Camera CAM72 | CAM70 | CAM71M x2











# WITH TRACKING CCTVHDR7T





7"

SCREEN

SSD 1 TB

FREE HARD DRIVE

Includes a 12 month subscription to the Guardian Telematics portal - Please contact sales office for more information

FMB641 - Tacho upgrade available on request

## 1TB SSD 5 CAMERA HD BESPOKE DVR SYSTEM

## **CCTVHDR8**

- 10 32 volt
- 5 x HD Cameras
- Key Lockable Data Storage up to 1TB SSD and 1 x 128GB SD Card
- 1TB SSD (solid-state drive) Hard Drive Included
- GPS Data | External Cameras Rated IP67
- Panic/incident button manually mark and safeguard an incident
- Monitor: H.115 mm W.175 mm D.25 mm (Excl. Stand) **DVR7HD**: H.50 mm W.165 mm D.152 mm



CAMERA OPTIONS

CUSTOMER TO CHOOSE CAMERA OPTIONS

#### INCORPORATES:

Recorder DVR8HD

Camera CAM73 | CAM70 | CAM71M x2

# WITH TRACKING CCTVHDR8T

- Built in G-Force Sensor



FMB641 - Tacho upgrade available on request

















# **CCTV SYSTEMS & VEHICLE SAFETY** 360° RECORDING SYSTEM | ACCESSORIES

# 4 CAMERA 360° PANORAMIC HD SYSTEM

ELIMINATES BLIND SPOTS TO ENSURE SAFE MANOEUVRING FOR RIGID OR COMMERCIAL VEHICLES

#### **CCTV360**

- 10 32 volt
- 7" LCD Touch Screen
- Camera Rated IP69K
- Front Collision warning
- Al Function
- Lens Angle 170° with Night Vision
- Up to 1TB SD card capacity DVR recording (2 card slots)
- 32GB SD card included
- ECE R10 Approved
- Monitor: H.112 mm W.192 mm D.30 mm (Excl. Visor) Camera: H.36 mm W.60 mm D.40 mm

DVR. H.40 mm W.140 mm D.123 mm



## CAM76

ALTERNATIVE CAMERA **OPTION AVAILABLE** 



CALIBRATION MATS

MAT1

\*Required for initial setup

- 2D or 3D viewing option
  All four camera images are processed, corrected, stitched together and displayed in real time
  1TB Capacity DVR journey recorder incorporated

INCORPORATES: Recorder | Monitor MON33 | Camera CAM75 x4 | Full Fitting Kit

## **HD 360° CAMERA OPTIONS**

- 12 volt (powered by CCTV360 control ECU)
- 10 metre lead (LEAD45)
- Lens anale 170°
- Rated IP69K
- 15 metre lead available (LEAD46)
- 4 Pin aviation connection | 3M Mounting Pad
  - ECE R10 Approved
  - H.36 mm W.60 mm D.40 mm



#### **CAM75**

- 3M Mounting Pad
- H.36 mm W.60 mm D.40 mm



#### **CAM76**

• H.50 mm W.80 mm D.75 mm









360° K/

# CCTV360 HD CAMERA LEADS

#### IFAD45

• 10 Metre HD Camera Lead extension between the control unit and camera

#### LEAD46

• 15 Metre HD Camera Lead extension between the control unit and camera



For use with: CCTV360 | CAM75 | CAM76

#### 7" HD CCTV360 MONITOR

#### **MON33**

- 10 32 volt
- 7" LCD touch screen monitor
- Remote Control
- 6 pin connection specific to the 360 kit
- ECE R10 Approved
- H.112 mm W.192 mm D.30 mm (Excl. Visor)







# **DVR RECORDING TIMES**

# x4 CAMERAS

RECORDING QUALITY	SSD STORAGE CAPACITY	BIT RATE	RECORDING TIME
1080P	2 TB	4Mbps	298 Hours
720P	2 TB	2Mbps	596 Hours
DI	2 TB	1Mbps	1193 Hours
1080P	1 TB	4Mbps	150 Hours
720P	1 TB	2Mbps	298 Hours
DI	1 TB	1Mbps	596 Hours
1080P	500 GB	4Mbps	75 Hours
720P	500 GB	2Mbps	149 Hours
DI	500 GB	1Mbps	298 Hours

# SD CARD STORAGE CAPACITY

1080P	32 GB	24Mbps	160 Mins
1080P	64GB	24Mbps	320 Mins
1080P	512GB	24Mbps	2560 Mins



G

# G

# DIRECT VISION PROGRESSIVE SAFE SYSTEM (PSS)

# Guidance for HGV Operators in Greater London

From October 2024 only HGVs over 12 tonnes rated three stars and above, or those with a PSS fitted, will be allowed on London's streets.


The changes aim to further enhance the safety standards of HGVs and reduce the risk of serious collisions and fatalities on London's streets.

# **SUMMARY OF PSS REQUIREMENTS**

- 1. A camera monitoring system must be fitted to the nearside of the vehicle, to eliminate all remaining blind spots
- 2. Class V and VI mirrors, or an equivalent camera monitoring system must be fitted to the front and nearside of the vehicle
- 3. A blind spot information system (BSIS) with active sensors that gives adequate warning to the driver of the presence of a vulnerable road user, must be fitted to the nearside of the vehicle

Must comply with UNECE Regulation 151

- 4. A moving off information system (MOIS) must be fitted to the front of the vehicle to warn the driver of the presence of a vulnerable road user - Must comply with UNECE Regulation 159
- 5. Side under-run protection must be fitted to both sides of the vehicle, except where this is demonstrably impractical
- 6. An audible vehicle manoeuvring warning must be fitted to provide an adequate audible warning to vulnerable road users when a vehicle is turning left
- External pictorial stickers and markings must be displayed on vehicles to provide adequate visual warning to vulnerable road users of the hazards present around the vehicle



# G

# FROM OCTOBER 2024 UPDATED REQUIREMENTS



# CCTV SYSTEMS & VEHICLE SAFETY **DVS PSS SAFETY SYSTEMS**

## **FULL RADAR SYSTEM**

DVSK3

KIT INCLUDES:

Moving Off Information System UNECE Regulation 159 MOIS

BSIS Blind Spot Information System

**UNECE Regulation 151** 

CAM33 **HD Side Mounted Camera** 

MON27QHD HD 7" Quad Monitor

4 camera inputs for future additions as required Single, split, triple or quad viewing options.

RA19 Left Turn Alarm

WAR2 'Blind Spot' Safety Sign - A3 Size The complete Progressive Safe System Compliant Electrical & Signage Kit

For vehicles with no Direct Vision kit

**currently fitted** (no side camera or left turn alarm)

#### RADAR UPGRADE KIT

## DVSK4

KIT INCLUDES:

Moving Off Information System UNECE Regulation 159 MOIS

**BSIS** Blind Spot Information System

UNECE Regulation 151

WAR2 'Blind Spot' Safety Sign - A3 Size

For vehicles with operational near side camera and audible left turn alarm already fitted



Upgrade compatible with any original DVS kit

# PART RADAR SYSTEM

#### DVSK5

KIT INCLUDES:

**BSIS** Blind Spot Information System

UNECE Regulation 151

CAM33 HD Side Mounted Camera

MON27QHD HD 7" Quad Monitor

4 camera inputs for future additions as required

Single, split, triple or quad viewing options.

RA19 Left Turn Alarm

WAR2 'Blind Spot' Safety Sign - A3 Size



START YOUR COMPLIANCE JOURNEY



Blind spot

Take care





Spread the cost with a Side Radar System

Front MOIS system will need to be added before October 24

# **PSS CALLIBRATION KIT**

# CAL<sub>1</sub>

- · Calibration kit is required for initial MOIS/BSIS setup
- Essential for setting the zones and time to collision configuration parameters
- H 66 mm W104 mm D 27 mm





# CCTV SYSTEMS & VEHICLE SAFETY SAFETY SYSTEMS

## MOVING OFF SYSTEM

#### **MOIS**

- 9 36 volt
- UNECE 159 compliant
- · Rated IP67
- Detection range 50m
- H.95 mm W.127 mm D.28 mm (Radar)
- H.50 mm W.50 mm D.48 mm (Display screen)

For use with: DVS PSS KITS



**BSIS** 

- 10 32 volt
- UNECE 151 compliant | Rated IP67

**BLIND SPOT SYSTEM** 

- FOV angle (vertical) 30° (horizontal) 150°
- · Modulation mode FMCW
- H.81mm W.139mm D.54mm (Sensor)
- H.25 mm W.84 mm D.88 mm (Control box)
- H.50 mm W.40 mm (Warning indicator)

For use with: DVS PSS KITS



# **DVS ELECTRICAL & SIGNAGE SAFETY SYSTEM**

#### DVSK1

KIT INCLUDES:

SDS1 Side Detection System

CAM12M Side Mounted Camera

MON24A 7" Monitor

SW100 Warning Alarm Override Switch

WAR1 'Blind Spot' Safety Sign





Take care



Compliant until October 24



The Guardian DVS Safe System conveniently provides the full range of electrical and signage requirements to be compliant with the current legislation.

Side detection control unit includes speed module and indicator trigger to assist with noise pollution

# **DVSK1 UPGRADE KIT (HARD DRIVE)**

**DVSU2** KIT INCLUDES:

CAM13A Rear View Camera | Lead CAM12M Side Mounted Camera | Lead CAM31 HD Front View Camera (Internal) | Lead

DVR4HD HD 4 Channel Digital Recorder



# FORS GOLD (>7.5T RIGIDS) COMPLIANT KIT

#### FORSK3

CCTVHDR7 4 Camera HD DVR Package

Includes: DVR7HD - HD Digital Recorder

MON70A - 7" HD Monitor

CAM72 - 1 x HD Front facing camera (internal)

CAM70 - 1 x HD Rear facing camera CAM71M - 2 x HD Side cameras

SDS1 Side Detection System

Includes: Interior warning display with buzzer

RA19 - External left turn warning alarm

SEN3-1x angled sensor SEN1 - 3 x under mount sensors

WAR1 "Blind Spot" Safety Sign 0897B "White Noise" Reverse Alarm

Full CCTV and side detection system kit containing all parts required for FORS Gold compliance





# **CCTV SYSTEMS & VEHICLE SAFETY** SAFETY SYSTEMS

#### SIDE DETECTION SYSTEM

#### SDS1

- 12 24 volt
- Sensors rated IP68
- E mark approved
- · Ultra sonic technology
- · Interior warning display with buzzer
- Intelligent cyclist / pedestrian anti collision system
- Intelligent external audible warning alarm
- System activated via indicator trigger and speed sensor signal (Other configurations are available on request including straight sensor SEN2)







SYSTEM INCLUDES:

SEN3 1 x angled sensor

SEN1 3 x under mount sensors

Control box RA19

Reverse alarm

Interior warning display

Full fitting kit

# SIDE DETECTION SYSTEM WITH ADDITIONAL FEATURES

#### SDS2

- IMPROVES SAFETY & FITTING TIME
- GPS Speed Sensor no wiring required
- Multi Function Triggered Alarm left turn, right turn, vehicle reversing
- Programmable Sensors distance can be selected to suit application
- Auto Mute Function during night hours via GPS signal
- · Self Diagnostic automatically feeds back any sensor faults
- Easy Installation wiring protected by conduit tubing
- 3 Year Warranty manufacturer confidence





#### FRONT DETECTION SYSTEM

Designed to prevent accidents with cyclists or pedestrians. At traffic lights, or in slow moving traffic, cyclists will often attempt to pass in front of a vehicle and similarly pedestrians will stand too close to the road not realising that a large vehicle turning left may cut across the curb. The FSDS1 pedestrian / cyclist detection system is an ultrasonic sensor system specifically designed to give a warning not only for the driver, but also to make cyclists and pedestrians aware of a vehicle manoeuvring

# FSDS1

- 12 24 volt
- Sensors rated IP68
- E mark approved
- Ultra sonic technology
- · Interior warning display with buzzer
- Intelligent cyclist / pedestrian anti-collision system
- System activated via indicator trigger and speed sensor signal via GPS



pedestrians and cyclists, the four sensors are mounted along the front at a height no than 450mm from the ground.







KIT INCLUDES: 4 x sensors To give best coverage to detect Control box Interior warning display Full fitting kit

#### FLEET TRACK DRIVER BEHAVIOUR MONITOR

#### MT2640

- · Hard Wired To Vehicle with Battery Back Up and European Roaming Sim
- Full GPS Tracking via PC and any smart device
- Full Telematics Reporting | Driver ID Enabled
- · Remote Vehicle Immobilisation Enabled Additional Hardware required
- · Driver Behaviour Monitoring | Reporting
- Automated Alerts | Live Reports | Historic Reports
- · Built in G-Force Sensor

Suitable for all vehicles (Cars, LCV/HGV, Plant & Machinery 12V/24V)

Requires a subscription to the Guardian Telematics portal, ask us for more details



## 4G RECHARGEABLE GPS ASSET TRACKER

#### **MAGTRACK 2**

- · Thatcham Approved
- Compact standalone (No wiring) waterproof tracker with up to a 5 year rechargeable battery
- Simple to attach with built in strong magnetic base, features an internal Vibration/Movement Sensor and Tamper/Removal sensor which are remotely programmed and alerted via an App for any smart device (Optional 24/7 monitored theft attendance)
- · Ideal for active tracking and secondary covert theft applications on all assets

Suitable for all vehicles (Caravans, Trailers, Containers, Horse Boxes, Campervans)

Requires a subscription to the Guardian Telematics portal, ask us for more details



H.30 mm W.105 mm D.60 mm



#### **BATTERY MOUNTED WATERPROOF TRACKER**

#### NANO

- Waterproof tracker that secures to the vehicle battery reducing the risk of removal
- · Bluetooth connectivity and an internal backup battery
- Does not conflict with any existing telemetry solutions already in situ
- · Self adhesive pad and clamp connectors for fast power cable connection to the car battery
- Up to 12 hours of internal backup battery
- Built-in accelerometer & gyroscope sensors with highly accurate impact/crash data

Suitable for all vehicles (Caravans, Trailers, Containers, Horse Boxes, Campervans)

Requires a subscription to the Guardian Telematics portal, ask us for more details



H.13 mm W.92 mm D.55 mm



# INCREASE YOUR RECOVERY PROBABILITY WITH THE STOLEN ASSET RECOVERY NETWORK (S.A.R.N)

#### Complimentary peace of mind S.A.R.N package included with MAGTRACK2 & NANO

You will be alerted by the app if your vehicle is being stolen.

You can confirm this by swiping a button. A 24/7 monitoring service will call you directly to offer support, guidance and updates.

You can track the vehicle yourself or press the 'HOLD TO RECOVER' button. A trained nationwide security member will be deployed and aim to secure your vehicle within 60 minutes of it stopping. Their remit is to secure and wait with the vehicle for up to 24 hours.



# Using S.A.R.N Recovery increases the chances of recovering your asset by up to 93%

Requires a subscription to the Guardian Telematics portal. One off recovery charge if activated. Please ask for more information.

ttraditional standard recovery methods are between 2% - 8% successful depending on industry. When using the app support system with an immediate action response this climbs rapidly to a very a successful recovery rate of 89





# CCTV SYSTEMS & VEHICLE SAFETY

# **TELEMATICS | JOURNEY RECORDERS**

## TRACKER WITH ON BOARD DIAGNOSTICS

#### **CARBIT**

- Plugs directly into Vehicle OBD Port (On Board Diagnostic Port)
- Full GPS Tracking via PC and any smart device
- Driver Behaviour Monitoring | Reporting/Scoring
- Built in G-Force Sensor monitors acceleration, deceleration and collision incidents
- Ruggedized Anti-Tamper Unit with battery disconnection alerts
- Full Telematics Reporting and Alerts: Braking | Acceleration | Cornering | Impact
- Voltage | Battery | Tamper | Speeding | Speed Threshold | Service Inspection
- · Live Reports | Historic Reports

Suitable for non HGV 12v vehicles manufactured after 1996 (Cars, Vans & Light Commercial)

Requires a subscription to the Guardian Telematics portal, ask us for more details



H.33 mm W.49 mm D.25 mm

# TELEMATICS, DRIVER MONITORING & INCIDENT FOOTAGE

#### JR5T

#### KIT INCLUDES

- DVR9HD HD Compact Digital Recorder H.28 mm W.114 mm D66 mm (smallest on the market)
- CAM72 HD Front facing camera (internal)
- 12 Months Telematics Subscription







Up to 4 additional cameras available including DMS (driver monitoring) **CAM74**, ask us for more details

# **4K HD JOURNEY RECORDER**

#### JR3

- 12 24 volt
- 4K 1080p Full HD
- WIFI Option | G-Sensor
- · Cyclic Recording
- 150° Wide Angle Lens
- H.64mm W.73mm D.32mm













FREE

# **4K DUAL CAMERA HD JOURNEY RECORDER**

#### JR4

- 12 24 volt
- 4K 1080p Full HD
- WIFI Option | G-Sensor
- · Cyclic Recording
- 150° Wide Angle Lens
- H.64mm W.73mm D.32mm







- 8 x LED Lights with Night Vision
- Backup Parking Camera Function
- Rated IP67









FREE SD CARD





# **CCTV SYSTEMS & VEHICLE SAFETY** MIRROR MONITORS

# 7" CEILING MOUNT MIRROR **MONITOR**

#### **GMMK**

- 12 volt
- · Mirror Monitor with roof mounting kit
- Monitor Resolution: 480 x 234
- H.108 mm W.250 mm D.23 mm







#### 7" LCD MIRROR MONITORS

#### **GMUK**

- 12 volt
- Universal Fit
- Monitor Resolution: 480 x 234
- RCA video connection
- H.108 mm W.250 mm D.23 mm

#### **GMCK**

- As above
- Clips over existing mirror D.38 mm







# 4.3" FORD TRANSIT MIRROR KIT

#### **GMTK**

- 12 volt
- Monitor Resolution: 480 x 272
- Mirror Monitor with stalk | 6 Night vision LEDs
- Monitor: H.82 mm W.270 mm D.46 mm Camera: H.51 mm W.387 mm D.102 mm













# 7" MERCEDES SPRINTER MIRROR KIT

#### **GMSK**

- 12 volt
- Monitor Resolution: 480 x 272
- Mirror Monitor with stalk | 6 Night vision LEDs
- Monitor: H.108 mm W.250 mm D.23 mm Camera: H.45 mm W.343 mm D.65 mm















# 7" VAUXHALL VIVARO MIRROR KIT

#### **GMVK**

- 12 volt
- Monitor Resolution: 480 x 234
- Mirror Monitor with stalk | 9 Night vision LEDs
- Monitor: H.108 mm W.250 mm D.23 mm Camera: H.80 mm W.235 mm D.75 mm













# 7" FIAT DUCATO MIRROR KIT

INCORPORATES: Monitor GMUK | Camera CAMS1

# **GMDK**

- 12 volt
- · Monitor Resolution: 480 x 234
- Mirror Monitor with stalk | 6 Night vision LEDs
- Monitor: H.108 mm W.250 mm D.23 mm Camera: H.58 mm W.263 mm D.65 mm

INCORPORATES: Monitor GMUK | Camera CAMD1















INCORPORATES: Monitor GMUK | Camera CAMV1



# CCTV SYSTEMS & VFHICLE SAFETY **BRAKE LIGHT CAMERAS**

# FIAT DUCATO | CITROËN RELAY PEUGEOT BOXER

- 1/4" CMOS image sensor
- TV system: PAL
- Audio Function
- 170° viewing angle
- Resolution: 6482 x 488
- 6 Night vision LEDs
- Mirror Image
- Rated IP68 | E Mark Approved
- H.58 mm W.263 mm D.65 mm





#### **FORD TRANSIT**

#### CAMF1

- 1/3" CMOS image sensor
- TV system: PAL
- Audio Function
- 120° viewing angle • Resolution: 762 x 504
- Mirror Image

• 6 Night vision LEDs

- Rated IP67 | E Mark Approved
- H.51 mm W.387 mm D.102 mm





## FORD TRANSIT 2012+ CUSTOM

#### CAMF2

- 1/3" CMOS image sensor
- TV system: PAL
- 120° viewing angle
- Resolution: 700 TVL
- Mirror Image
- Rated IP67 | E Mark Approved
- H.67 mm W.262 mm D.95 mm





# **FORD TRANSIT 2016+ CUSTOM**

#### CAMF3

- 1/3" CMOS image sensor
- TV system: PAL
- 120° viewing angle
- · Resolution: 700 TVL
- 9 Night vision LEDs
- Mirror Image
- Rated IP67 | E Mark Approved
- H.67 mm W.262 mm D.95 mm





# MERCEDES SPRINTER VW CAMPER (PAL)

#### CAMS1

- 1/3" CMOS image sensor
- TV system: PAL
- Audio Function
- 130° viewing angle
- Resolution: 762 x 504
- 6 Night vision LEDs
- Mirror Image
- Rated IP67 | E Mark Approved
- H.45 mm W.343 mm D.65 mm



# VAUXHALL VIVARO 2014+ **RENAULT TRAFFIC 2014+**

## CAMV1

- 1/4" CMOS image sensor
- TV system: PAL
- Audio Function
- 170° viewing angle • Resolution: 762 x 504
- 9 Night vision LEDs
- Mirror Image
- Rated IP67 | E Mark Approved
- H.80 mm W.235 mm D.75 mm





# MERCEDES VIANO | VITO

#### CAMV2

- · Replaces number plate light
- 1/4" CMOS image sensor
- Resolution: 580 x 492 | Lens: F1.8
- · System: NTSC
- 170° viewing angle
- RCA video connection
- Mirror Image
- Rated IP66
- H.31 mm W.75 mm D.32 mm



# CAN'T FIND YOUR MAKE OR MODEL?

We have access to an extensive range of brake light cameras.

Contact us for more details.

# CCTV SYSTEMS & VEHICLE SAFETY **MONITORS**

# 5" MONITOR

#### MON23A

- 10 32 volt
- 3 Camera Inputs with Mirror or Normal Switching
- · Remote Control
- H.117 mm W.157 mm D.30 mm (Excl. Visor)



For use with: CAM13A | CAM12M | CAM18A







## 5.6" DIGITAL MONITOR

#### MON13B

- 10 32 volt
- 3 Camera Inputs with Mirror or Normal Switching
- Remote Control | HD Compatible
- H.136 mm W.145 mm D.31 mm (Excl. Visor)



For use with: CAM13A | CAM12M | CAM18A









# 5.6" DIGITAL MONITOR

MON14A (Upgrading to HD in 2024)

- 10 32 volt
- 3 Camera Inputs with Mirror or Normal Switching
- · Remote Control
- H.118 mm W.160 mm D.22 mm (Excl. Visor)



For use with: CAM13A | CAM12M | CAM18A





# 7" HD WEATHERPROOF MONITOR

#### MON19HD

- 10 32 volt
- 3 Camera Inputs with Mirror or Normal Switching
- Remote Control | Automatic self-adjusting resolution
- H.132 mm W.197 mm D.35 mm (Excl. Visor)



For use with: CAM30 | CAM31 | CAM33









# 7" MONITOR

#### MON24A

- 12 24 volt
- 2 Camera Inputs with Mirror or Normal Switching
- · Remote Control
- H.115 mm W.172 mm D.44 mm (Excl. Visor)



For use with: CAM13A | CAM12M | CAM18A







# 7" HD MONITOR

#### **MON30**

- 10 32 volt
- 7" LCD touch screen monitor
- 1x HDMI input
- Remote Control | Audio function
- H.114 mm W.193 mm D.30 mm (Excl. Visor)



For use with: DVR4HD | DVR6







# CCTV SYSTEMS & VEHICLE SAFETY **MONITORS**

## 7" 1080P HD MONITOR

- 12 24 volt
- 1080p camera inputs with Mirror or normal switching
- D1/720p/1080p auto sensing
- Audio function
- Remote Control
- H.113 mm W.195 mm D.27 mm (Excl. Visor)







# AUDIO

# UP TO 3 CAMERAS



#### MON27HD

- · Single screen viewing
- 3 x camera inputs

For use with: CAM30 | CAM32 | CAM33 | CAM35

# 7" HD MONITOR

#### **MON31**

- 10 32 volt
- 7" LCD digital screen
- $3 \times D1/720 p/1080 p$  camera inputs
- Remote Control | Audio function
- H.122 mm W.184 mm D.26 mm (Excl. Visor)



For use with: CAM30 | CAM35 | CAM33



AUDIO FUNCTION





360° K/

## 7" HD MONITOR

• Single, split, triple or quad viewing options

#### MON32

MON27QHD

• 4 x camera inputs

- 10 32 volt
- 7" LCD touch screen monitor
- $3 \times D1/720 p/1080 p$  camera inputs
- 1x HDMI input
- Remote Control | Audio function
- H.114 mm W.193 mm D.30 mm (Excl. Visor)



For use with: CAM30 | CAM35 | CAM33











# 7" HD CCTV360 MONITOR

#### **MON33**

- 10 32 volt
- 7" LCD touch screen monitor
- Remote Control
- 6 pin connection specific to the 360 kit
- ECE R10 Approved
- H.112 mm W.192 mm D.30 mm (Excl. Visor)









# 7" HD TFT LCD MONITOR

#### MON70A

- 9 26 volt
- 7" HD LCD screen
- PAL/NTSC | 1080P HD resolution
- H.118 mm W.180 mm D.25 mm





5





For use with: CCTVHDR7 | CCTVHDR7T | CCTVHDR8 | CCTVHDR8T

# CCTV SYSTEMS & VEHICLE SAFETY MONITORS | CAMERAS

# 7" HD WIRELESS DIGITAL MONITOR WITH DVR

#### MON15HD

- 10 32 volt | 4 Programmable Camera Inputs
- 1 SD Card Slot up to 128GB (32GB Supplied)
- · Remote Control
- H.122 mm W.182 mm D.42 mm (Excl. Visor)

For use with: CCTV15HD | CAM15HD











# 7" WIRELESS QUAD MONITOR WITH DVR

#### MON26D

- 10 32 volt | 4 Programmable Camera Inputs
- 1 SD Card Slot up to 128GB (32GB Supplied)
- · Remote Control
- H.140 mm W.190 mm D.76 mm (Excl. Visor)

For use with: CCTV26D | CAM26D







SD



# SIDE MOUNTED CAMERA

#### CAM12M

• 12 volt (12 - 24 volt via monitor) • CMOS Module

SD

- 5 metre lead (LEAD20)
- Lens Angle 140° with Night Vision
- H.45 mm W.58 mm D.73 mm



# SLIMLINE NUMBER PLATE CAMERA

#### CAM14

- 12 volt (12 24 volt via monitor)
- 5 metre lead included (LEAD20)
- Lens Angle 180° with Night Vision
- CCD Module
- Rated IP69K
- H.30 mm W.200 mm D.25 mm







For use with:



# **REAR CAMERAS**

- 12 volt (12 24 volt via monitor)
- 20 metre lead (LEAD 19)
- Lens angle 120° with night vision
- CMOS Module
- · Audio Function
- Rated IP69K
- H.80 mm W.74 mm D.77 mm

CAM13A - Black

CAM13W - White

#### CAM13C

Available without 20 metre lead (LEAD 19)













# **CCTV SYSTEMS & VEHICLE SAFETY CAMERAS**

## TWIN LENS CAMERA

#### CAM16

- 12 volt (12 24 volt via monitor)
- 2 x 20 metre lead (LEAD19)
- Each Lens Angle 120° with Night Vision
- CMOS Module | Rated IP67
- H.85 mm W.115 mm D.65 mm







For use with:

## **ROOF MOUNTED CAMERA**

#### CAM18A

- 12 volt (12 24 volt via monitor)
- 5 metre lead included (LEAD20)
- 150° Viewing Angle
- Night Vision up to 10 metres
- Rated IP69K











# COMPACT SWIVEL CAMERA

- 12 volt (12 24 volt via monitor)
- 5 metre lead included (LEAD20)
- 120° Swivel Camera Lens | CMOS Module
- 5 x Night Vision LEDs | Rated IP69K
- H.50 mm W.60 mm D.45 mm

#### **CAM23**

· Normal Image

# CAM24M

• Mirror Image





360°





# DRIVER MONITORING CAMERA (DMS) (INTERNAL)

#### **CAM74**

- 12 24 volt via monitor
- · Self calibration to driver's face
- · Movement activation will not trigger when vehicle is
- · Distraction detection Sleep detection Audible in cab alarm
- · Automatic video upload when connected to IncidentCam 4G
- H.30 mm W.83 mm D.43 mm





12-24 Volt
MULTI VOLTAGE

For use with: JR5T



# **HD 360° CAMERA**

#### **CAM75**

- 12 volt (powered by CCTV360 control ECU)
- 10 metre lead (LEAD45)
- Lens angle 170° | Rated IP69K
- 4 Pin aviation connection | 3M Mounting Pad
- ECE R10 Approved
- H.36 mm W.60 mm D.40 mm
- 15 metre lead available (LEAD46)









# **HD 360° CAMERA**

#### **CAM76**

- 12 volt (powered by CCTV360 control ECU)
- 10 metre lead (LEAD45)
- Lens angle 170° | Rated IP69K
- 4 Pin aviation connection
- ECE R10 Approved
- H.50 mm W.80 mm D.75 mm









# CCTV SYSTEMS & VFHICLE SAFETY **CAMERAS**

# **HD DIGITAL WIRELESS REAR CAMERA**

#### CAM15HD

- 10 32 volt
- · Lens Angle 120° with Night Vision
- CMOS Module | Rated IP69K
- H.72 mm W.98 mm D.70 mm



# **DIGITAL WIRELESS REAR CAMERA** CAM26D

- 10 32 volt
- 9 x IR LEDs for Night Vision
- CMOS Module
- · Lens Angle 120°
- · Rated IP67
- · Audio Function
- H.100 mm W.95 mm D.60 mm



WIRELESS



IP67 RATED WATERPROOF



For use with: CCTV26D | MON26D

# **HD REAR CAMERA**

#### **CAM30**

- 12 volt (12 24 volt via monitor)
- 20 metre lead (LEAD41)
- Lens angle 120° with 45ft night vision
- HD 1080p Sony CCD chipset | 18 x SMD LEDs
- 4 pin aviation connector | Audio function
- Day / night sensor for auto adjustment

• H.77 mm W.90 mm D.70 mm



# **HD FRONT CAMERA** (INTERNAL)

#### CAM31

- 12 volt (12 24 volt via monitor)
- 5 metre lead (LEAD18)
- Lens angle 130° with night vision
- 1080p 1/2.8 Sony CMOS image device
- · WDR function | Normal image for front viewing

• H.62 mm W.45 mm D.60 mm





WIDE DYNAMIC RANGE (WDR)



For use with: CCTV19HD | CCTV27HD | CCTV27QHD

# HD DUAL VIEW CAMERA (INTERNAL)

#### CAM32

(Twin camera, one facing forward recording the road, one facing into the cab recording the driver)

- 12 volt (12 24 volt via monitor)
- 2 x 5 metre lead (LEAD18) | Lens angle 130° with night vision
- 1080p 1/2.8 Sony CMOS image device | 4 x night vision LEDs
- · Normal image for front viewing
- · Mirror image for viewing driver/passenger
- H.62 mm W.85 mm D.60 mm



# **HD SIDE CAMERA**

#### CAM33

- 12 volt (12 24 volt via monitor)
- 5 metre lead (LEAD42)
- Lens angle 120° with 45ft night vision
- + HD 1080p Sony CCD chipset  $\mid$  10 x SMD LEDs
- Mirror image | Day/night sensor for auto adjustment
- 4 pin aviation connection

• H.60 mm W.78 mm D.98 mm











# **CCTV SYSTEMS & VEHICLE SAFETY CAMERAS**

# **HD DOME CAMERA** (INTERNAL)

#### **CAM34**

- 12 volt (12 24 volt via monitor)
- 5 metre lead (LEAD18)
- · Lens angle 150° with night vision
- 1080p 1/2.9 Sony CMOS image device
- Mirror image | Day / night sensor for auto adjustment
- H 46 mm Dig 75 mm



# **HD FRONT CAMERA** (INTERNAL)

#### **CAM35**

- 12 volt (12 24 volt via monitor)
- 5 metre lead (LEAD42)
- Lens angle 120° with adjustable vertical 50° angle
- Sony CMOS sensor | WDR and Night vision
- · Adhesive adjustable 3M mount
- · 4 Pin aviation connector
- ECE R10, EMC, CE Approved
- H.40 mm W.65 mm D.140 mm



# **HD REAR CAMERA**

#### CAM70

- 12 volt (12 24 volt via monitor)
- 20 metre lead (LEAD41)
- Lens angle 170° with night vision
- Sony CCD image module
- Rated IP68 | 4 pin connection
- H.63 mm W.75 mm D.70 mm



# **HD SIDE CAMERA**

#### CAM71M

- 12 volt (12 24 volt via monitor)
- 5 metre lead (LEAD42)
- Lens angle 170° with night vision
- · Sony CCD image module
- · Rated IP68
- 4 pin connection
- H.45 mm W.58 mm D.76 mm





For use with:







# **HD FRONT CAMERA (INTERNAL)**

#### CAM72

- 12 volt (12 24 volt via monitor)
- 5 metre lead (LEAD42)
- Lens angle 170° | Sony CCD image module
- 4 pin connection | Adhesive adjustable 3M mount
- H.45 mm W.56 mm D.39 mm



# **HD DUAL VIEW CAMERA (INTERNAL)**

#### CAM73

(Twin camera, one facing forward recording the road, one facing into the cab recording the driver)

- 12 24 volt
- 720p Resolution | AHD Format
- Sony 'Starlight' 150° Front facing Lens
- Internal Facing Lens 160° includes IR for Night Vision
- 3M VHP Mounting Pad
- H.42 mm W.66 mm D.39 mm











# **CCTV SYSTEMS & VEHICLE SAFETY** RECORDERS

# **HD 4 CHANNEL DIGITAL RECORDER**

#### **DVR4HD**

- 10 32 volt
- Al Function
- 4 camera inputs (mixed resolution recording options 1080P/720P/D1)
- · Key Lockable data storage up to
- 1 x 1TB SSD hard drive and 1 x 128GB SD card
- 500GB Hard Drive Included
- · Optional password protection
- Multiple recording modes Power-on, Scheduled, Cyclic, G-sensor, Motion Detection, Overspeed and Emergency
- Up to 600 hrs recording
- PC playback software | Remote Control
- H.38 mm W.146 mm D.185 mm















For use with:

# **HD 8 CHANNEL DIGITAL RECORDER**

#### DVR6

- 10 32 volt
- 8 camera inputs (mixed resolution recording options 1080P/720P/D1)
- Key Lockable data storage up to
- $1\,x$  1TB SSD hard drive and  $1\,x$  128GB SD card
- 500GB Hard Drive Included
- · Optional password protection
- Multiple recording modes Power-on, Scheduled, Cyclic, G-sensor, Motion Detection, Overspeed and Emergency
- Up to 300 hrs recording
- PC playback software | Remote Control
- H.100 mm W.226 mm D.225 mm











For use with:



# **HD DIGITAL RECORDER**

- 10 32 volt
- VGA output (to MON70A)
- Lockable key data storage up to 1 x 1TB SSD hard drive and 1 x 128GB SD card option
- 1TB SSD Hard Drive Included
- 4 trigger inputs | GPS data
- Flash drive port for convenient data transfer
- Panic/incident button | Remote Control
- H.50 mm W.165 mm D.152 mm

**DVR7HD** - 4 camera inputs

DVR8HD -5 camera inputs





SSD 1TB



For use with:







# CCTV SYSTEMS & VEHICLE SAFETY

# BRIGADE REVERSE | SIDE DETECTION SYSTEMS

# **BRIGADE SIDESCAN SENSOR SYSTEM (SS-4100W)**

#### 5257

- 12 24 volt
- 4 sensor system
- 1.0 / 1.5m detection range (selectable via dip switch)
- Audible distance warning
- Underslung and flush-mount fixings included
- 2 Levels of sensitivity (selectable via dip switch)
- · Obstacles detected in under 200 milliseconds
- · Self-diagnostic function
- Operating temp -40 to +80°C





## BRIGADE BACKSCAN SENSOR SYSTEM (BS-4000W)

#### 3744

- 12 24 volt
- · 4 sensor system
- 2.5m detection range outer sensor 2.5m/0.6m (selectable via dip switch)
- Graduated visual and audible distance warning display
- Underslung and flush-mount fixings included
- Obstacles detection in under 200 milliseconds
- · Self-diagnostic function
- Operating temp -40 to +80°C





SENSORS

# BRIGADE RECOMMENDED ADDITIONS FOR ARTICULATED VEHICLES

#### **SENSOR KIT (SK-UDS-05)**

4219

 Truck / Trailer sensor only cable kit



# **BUZZER/DISPLAY** CABLE (UDS-10BC)

• 10m Buzzer / Display Cable



# BRIGADE TRAILER SENSOR CABLE KIT

(SK-15-04)

3997

Truck / Trailer Camera Sensor Cable Kit



## SPEED TRIGGER MODULE (LS-60-A)

#### 4851

- 12 24 volt
- · Low speed trigger module
- For use with 3744



## **LEFT TURN** WARNING **ALARM**

#### 1334

- 12 24 volt
- 4 Bolt Fixing | 90dB
- · Single Side Turn Message Caution Vehicle Turning Left"
- · CE, EMC Approved
- L.122 mm H.84 mm W.50 mm





IP68 RATED WATERPROO

# TURN INDICATOR TRIGGER (TS-0001ECU)

#### 1362

- 12 24 volt
- · Turn indicator trigger
- For use with 5257





# CCTV SYSTEMS & VEHICLE SAFETY **LEADS**

#### **CCTV CAMERA EXTENSION LEADS**

· Camera Lead Extension between the Monitor and Camera

LEAD17 - 20 metre lead

LEAD18 - 5 metre lead



For use with:

CCTV13B | CCTV14A | CCTV18A | CCTV19HD CCTV23A | CCTV24A | CCTV27HD | CCTV27OHD

#### **CCTV CAMERA LEADS**

· Standard Camera Lead for connecting the Camera to the Monitor Harness

LEAD19 - 20 metre lead

LEAD20 - 5 metre lead



For use with:

CCTV13B | CCTV14A | CCTV18A | CCTV23A | CCTV24A

#### **CCTV CAMERA LEAD**

#### LEAD21

• Y Piece Camera Lead Adaptor which allows a single Camera to be connected in to 2 different devices at once (DVR & Monitor)



For use with: DVR4HD | CCTV13B | CCTV14A | CCTV18A CCTV19HD | CCTV23A | CCTV24A | CCTV27HD CCTV27QHD

#### CAMERA CONVERSION LEAD

#### LEAD22

 This Camera Conversion Lead has been developed to allow compatibility between Guardian Cameras and various other systems.

Please contact the Technical Department for clarification.



For use with:

CAM12M | CAM13A | CAM13C | CAM14 CAM16 | CAM18A | CAM23 | CAM24M

#### CAMERA CONVERSION LEAD

#### LFAD23

 This Camera Conversion Lead converts analogue Camera Leads (LEAD19/LEAD20) to accept HD Cameras



# ARTICULATED VEHICLE 7 PIN SUZI-LEAD CONNECTION KIT

## LEAD10

- 1x Plastic 7 Pin Socket. 5 Metre Lead (Monitor Side)
- 1 x Plastic 7 Pin Socket, 20 Metre Lead (Camera Side)
- 1x7 Core Suzi Coil with 3 Metre Working Length




For use with:

CCTV13B | CCTV14A | CCTV18A | CCTV23A | CCTV24A

# **HD ARTICULATED VEHICLE 7 PIN** SUZI-LEAD CONNECTION KIT

## LEAD10HD

- 1 x Plastic 7 Pin Socket, 5 Metre Lead (Monitor Side)
- 1 x Plastic 7 Pin Socket, 20 Metre Lead (Camera Side)
- 1 x 7 Core Suzi Coil with 3 Metre Working Length
- 1x LEAD23







# ARTICULATED VEHICLE DEDICATED **5 PIN SUZI-LEAD CONNECTION KIT**

## LEAD13

- 1 x Plastic 5 Pin Socket, 5 Metre Lead (Monitor Side)
- 1x Plastic 5 Pin Socket, 20 Metre Lead (Camera Side)
- 1x5 Core Suzi Coil with 3 Metre Working Length



CCTV13B | CCTV14A | CCTV18A | CCTV23A | CCTV24A

# CCTV SYSTEMS & VEHICLE SAFETY **LEADS**

## ARTICULATED VEHICLE DEDICATED 7 PIN 2 CAMERA SUZI-LEAD

#### LEAD13T

- · Articulated vehicle dedicated 7 pin suzi lead connection kit
- 1x metal dedicated 7 pin socket split into 2 x 5 metre leads with female 4 pin aviation connection (monitor side)
- 1x dedicated 7 pin suzi coil (3 metre working length)
- 1x metal dedicated 7 pin socket split into 2 x 25cm leads with male 4 pin aviation connection (trailer side)



For use with: CCTV13B | CCTV14A | CCTV23A | CCTV24A

# ARTICULATED VEHICLE DEDICATED 5 PIN SUZI-LEAD CONNECTION KIT

#### LEAD17M

- 1 x Metal 5 Pin Socket, 5 Metre Lead (Monitor Side)
- 1x Metal 5 Pin Socket, 20 Metre Lead (Camera Side)
- 1x5 Core Suzi Coil with 3 Metre Working Length



For use with:

CCTV13B | CCTV14A | CCTV18A | CCTV23A | CCTV24A

# **SENSOR LEAD**

#### LEAD40

• 15 Metre extension Lead



For use with: SDS1

# **HD CCTV CAMERA LEADS**

 HD Camera Lead for connecting the Camera to the Monitor Harness

#### LEAD41

· 20 Metre

#### LEAD42

• 5 Metre



For use with: CAM70 | CAM71M | CAM72 | CAM30 CAM31 | CAM32 | CAM34 | CAM73 | CAM75 | CAM76

# **CCTV LEAD**

#### LEAD44

- Replacement 5 Pin suzi lead for articulated vehicle connection kit
- Please note this is purely a replacement part and will only work in conjunction with LEAD13



#### **POWER LEADS**

## PL14

• MON14A Power Lead

#### PL24

• MON24A Power Lead



#### **CAMERA CONVERSION LEAD**

#### RCA

- 1 Metre Camera Conversion Lead
- Converts from 2 x phono connections to 1 x 4 pin aviation screw type connector





# CCTV SYSTEMS & VEHICLE SAFETY ACCESSORIES

## **AERIALS**

#### AEL2

- Screw Fit
- Up to 90° folding angle
- H.138 mm

#### AEL3

- Magnetic Mount
- 3m Coax Extending Cable
- · H.186 mm Mag Base Diameter 46 mm

For use with: CCTV15HD | CCTV26D | MON15HD MON26D | CAM15HD | CAM26D



# MOUNTING KIT

SDS1 SENSOR

• For use with SDS1 Kit

• 2 Bolt Under Mount Sensor

SEN1

#### STALK1

• Roof Mounting Kit (Mirror sold separately)



For use with: GMMK | GMUK

## **SDS1 SENSOR**

#### SEN2

- For use with SDS1 Kit
- Straight Rubber push in Sensor

#### SEN3

- For use with SDS1 Kit
- Corner Angled Rubber Sensor



# **INTERIOR CAMERA ADHESIVE**

## GLUE

- · Loctite Adhesive
- For use with securing Mirror Mount Monitors to a vehicle windscreen
- Suitable for Metal and Glass



# "BLIND SPOT" SAFETY SIGN

- Self Adhesive Vinyl
- Portrait

WAR1 - A4 Size

WAR2 - A3 Size



# MICRO SD MEMORY CARDS

 Micro SD Memory Card with Adaptor

**SD32** - 32GB

**SD64** - 64GB

**SD512** - 512GB



# SOLID STATE HARD DRIVE

#### **HD500S**

• 500GB

## HD1TBS

• 1TB



\*Brand may vary



# CCTV SYSTEMS & VEHICLE SAFETY

# WARNING | BUZZERS | REVERSE ALARMS

#### **MINI BUZZER**

#### MB12

- 12 volt
- Black Mini Buzzer
- Single Point Fixing with Terminal Connections
- Dia. 39 mm H.34 mm



#### **MINI BUZZER**

#### MB24

- 24 volt
- · Red Mini Buzzer
- Single Point Fixing with Terminal Connections
- Dia. 39 mm H.34 mm



# BRIGADE SPEAKING **REVERSE ALARM**

#### 0077A

- 12 24 volt
- Real Speech Message "Shh! Stand Well Clear Vehicle Reversing"
- 4 Bolt Fixing
- · CE, EMC Approved
- L.122 mm H.84 mm W.50 mm











# BRIGADE MEDIUM DUTY WHITE NOISE REVERSE ALARM

#### 0897B

- 12 24 volt
- · 'White Noise' Multi Frequency Broadband Sound
- 4 Bolt Fixing
- · CE, EMC Approved
- L.105 mm H.65 mm W.32 mm











# **BRIGADE MEDIUM DUTY** WHITE NOISE REVERSE ALARM

#### 0934B

- 12 24 volt
- · 'White Noise' Multi Frequency Broadband Sound
- 4 Bolt Fixing
- CE, EMC Approved
- L.105 mm H.65 mm W.37 mm





92 IP68 RATED DECIBELS WATERPROOF





# WEATHERPROOF **REVERSING ALARM**

#### RA1

- 12 24 volt
- · Night Silent Function
- · Single Bolt Fixing
- Rated IP65
- Dia.70 mm L.87 mm









#### **REVERSING ALARM**

## RA3

- 12 volt
- · Night Silent Function
- · Single Bolt Fixing
- Rated IP54
- Dia.56 mm L.75 mm



#### **REVERSING ALARM**

# RA4

- 24 volt
- Night Silent Function
- · Single Bolt Fixing
- Rated IP54
- Dia.56 mm L.75 mm



# **CCTV SYSTEMS & VEHICLE SAFETY** WARNING | REVERSE ALARMS

# HALOGEN REVERSE LIGHT BULB WITH INTEGRAL REVERSE ALARM

- 75dB
- Dia.25 mm L.43 mm

#### RA6

- 12 volt
- Direct Replacement for 382 (BA15s)

#### RA7

- 24 volt
- Direct Replacement for 241 (BA15s)





# PRECO REVERSING ALARM

#### **RA10**

- 12 24 volt
- 4 Bolt Fixing
- 2 Wire Termination
- Temperature Range -40 to +77 Degrees
- L.100 mm H.83 mm W.41 mm

٥٥

₩









# PRECO HEAVY DUTY **REVERSING ALARM**

- 12 24 volt
- 4 Bolt Fixing
- Temperature Range -40 to +77 Degrees
- L.96 mm H.127 mm W.74 mm









# **REVERSING ALARM**

#### **DΔ15**

- 12 80 volt
- 4 Bolt Fixing
- E Mark Approved
- L.100 mm H.63 mm W.41 mm









# **SELF ADJUSTING REVERSING ALARM**

## **RA16**

- 12 48 volt
- Self Adjusts to 5dB above Surrounding Noise Level
- 4 Bolt Fixing
- E Mark Approved
- L.100 mm H.63 mm W.41 mm











## **REVERSING ALARM**

#### **RA17**

- 12 24 volt
- · Night Silent Function
- 4 Bolt Fixing
- E Mark Approved
- L.100 mm H.63 mm W.41 mm





97 IP67 RATED

DECIBELS WATERPROOF



**®ECCO**<sup>®</sup>

# SPEAKING LEFT TURN WARNING ALARM

#### **RA19**

- 9 32 volt
- Single Side Turn Message "Caution Vehicle Turning Left"
- 4 Bolt Fixing
- E Mark Approved
- L.110 mm H.70 mm W.40 mm









#### **ECCO REVERSE ALARM**

#### **RA20** Ecco No. 515-002



- · Night Silent Facility
- 4 Bolt Fixing
- Rated IP64
- ECE R10, CE Approved
- L.102 mm H.71 mm W.40 mm







# CCTV SYSTEMS & VEHICLE SAFETY

# WARNING | REVERSE ALARMS

# **ECCO DOUBLE ENGAGE REVERSE ALARM**

**RA21** 

Ecco No. 520-004



- 12 24 volt
- Double Engage Option for Driver
- 4 Bolt Fixing
- ECE R10, CE Approved
- L.102 mm H.71 mm W.40 mm











# **ECCO MULTI FREQUENCY REVERSE ALARM**

Ecco No. EA5050



- 12 24 volt
- Multi Frequency to Combat Noise Pollution
- 4 Bolt Fixing
- ECE R10, CE Approved
- L.102 mm H.71 mm W.40 mm











# PROGRAMMABLE MESSAGE ALARM

#### **RA27**

- 12 24 volt
- Programmable bespoke message via USB
- Supports MP3 files up to 4MB
- 2 Bolt Fixing with 300mm Cable Connection
- ECE R10, EMC, CE, RoHS Approved
- L.104 mm H.75 mm W.38 mm









#### **MULTI FUNCTION TRIGGERED ALARM**

#### **RA28**

- 12 24 volt
- x3 audible warnings: "Caution Vehicle is turning Left" "Caution Vehicle is turning Right" "Warning, this vehicle is Reversing"
- 5m Conduited Cable
- 6 Way Superseal Connector
- L.103 mm H.68 mm W.45 mm







IP68 RATED WATERPROOF



For use with: SDS2

# ASK US ABOUT OUR AUTOMOTIVE INTERFACES

We have access to a wide range of interfaces and rear cameras to suit specific vehicles Including Audi, Mercedes, Renault, VW

Please enquire with make, model and year for information and prices





